

NADYA

Features

- · Solid brass construction
- Quarter-turn washerless ceramic disc valve cartridges
- Spout assembly with integral supply hoses
- · Spring-loaded, normally closed lever handle
- 6-7/16" (16.4 cm) spout height at outlet
- 4-13/16" (12.2 cm) spout reach (c-c)
- 1 gallon (3.6 liters) per minute maximum flow rate*
- For single hole configurations

*A Water Dispenser flow rate of approximately 1 gpm or less is typical but will vary depending on installation specific factors including in-line water pressure and water filtration system.

Codes / Standards Compliance

Meets or exceeds the following at date of manufacture:

- ASME A112.18.1/CSA B125.1
- IAPMO/cUPC
- IPC
- NSF 61
- Energy Policy Act of 1992
- All applicable US Federal and State material regulations

Hot Water Dispenser Faucet

107H





Colors / Finishes

10B: Oil Rubbed Bronze
15: Polished Nickel
15S: Satin Nickel
26: Polished Chrome

 Other: Refer to the Newport Brass catalog for additional color/finish options.

Colors / Finishes

Specified Model		
Model	Description	Colors Finishes
107H	Hot Water Dispenser Faucet	☐ 10B ☐ 15 ☐ 15S ☐ 26 ☐ Other
5-036	Point-of-Use Water Heater (115V, 140° to 190° range)	

Product Specification: Add "Color / Finish" suffix to Model number, below.

The Hot Water Dispenser Faucet shall be made of solid brass construction. Faucet shall incorporate a spout assembly with integral supply hoses and feature a quarter-turn washerless ceramic disc valve cartridge. Faucet shall incorporate a contemporary hot lever handle. Hot Water Dispenser Faucet shall have a 1 gallon (3.6 liters) per minute maximum flow rate and accommodate single hole configurations. Product shall incorporate a 6-7/16" (16.4 cm) spout height at outlet and a 4-13/16" (12.2 cm) spout reach (c-c). Hot Water Dispenser Faucet shall be Newport Brass Model 107H/___. [Point-of-Use Water Heater shall be Newport Brass Model 5-036].

107H

Product Dimensions (units are in inches)



